

Therapy Manual

Model: ZA-37 www.drzamps.com



This symbol warns the user of dangerous voltage levels localized within the enclosure.



This symbol advises the user to read all accompanying literature for safely operating the unit

Important Safety Instructions

- 1) Read these instructions.
- 2) Keep these instructions.
- 3) Heed all warnings.
- 4) Follow all instructions.
- 5) Do not use this apparatus near water.
- 6) Clean only with dry cloth.

7) Do not block any ventilation openings. Maintain at least 3 feet of distance around all sides of amplifier. Do not block any ventilation openings with items such as newspapers, tablecloths, curtains, etc.

8) Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.

9) Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet. 10) Protect the power cord from being walked on or pinched particularly at plugs, convenience

receptacles, and the point where they exit from the apparatus.

11) Only use attachments/accessories specified by the manufacturer.

12) Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.

13) Unplug this apparatus during lightning storms or when unused for long periods of time.

14) Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.

15) Avoid placing any liquids on or near the amplifier that may splash or drip such as those contained in bottles, cans, glasses, etc.

*Dr Z amplifiers are capable of producing very high sound pressure levels which can cause temporary or permanent hearing damage.

*If any screw that is actually on the amp chassis needs to be replaced contact Dr Z Amps for the proper size. Screw size is critical for inner chassis clearances.

General Information

The Therapy is a departure from what Dr Z Amps has done in the past. We started with a clean sheet of paper and a fresh sonic perspective. The result is a cathode biased 6L6 based amp with a flavor of a low powered tweed Twin. It has a range of tones that will appeal to a wide audience and it includes a special design post phase inverter master volume which does not lose top-end definition at bedroom settings. Its output is a cool 35 watts with a tube rectified power supply.

Under the hood you'll find the highest quality components throughout. Special attention was used to select the coupling caps. We chose Jupiter hi end hand rolled coupling caps for the banana yellow Astron tone found in early Fender tweed amps. A high precision PEC sealed volume pot is used for unmatched sensitivity, control, and long life. The large output transformer gives more thrust than you can get from a 20 watt amp. The Therapy has a woody bass response that fills out nicely. Think tweed-like clean with a modern clarity. We incorporated our unique 2 preamp tube front end that we have mastered in designs from our past. The more American-type overdrive sounds are smooth and harmonically rich while allowing great sustain and clarity. Because the Therapy doesn't use a cascaded front end you also get great clarity from pedals even at the highest drive settings. This simple design coupled with special EQ wiring maximizes gain, touch dynamics, and guarantees stable frequency response across the dial.

The PPIMV helps keep the sound level in check whether you are in church or in an arena. In this circuit the master is very effective with better results than you would get from many attenuators. All in all the Therapy is a great choice for a modern spin on a 6L6 design. It has great cleans for the roots players and plenty of drive for the rockers.

Specifications

Power Output	35 watts
Output Tubes	2 - 6L6 STR
Preamp Tubes	2 - 12AX7
Rectifier	5AR4
Controls	Volume, Treble, Mid, Bass, Master
Configurations	Head
Colors	Black, Blonde, Red
Dimension & Weight	19"W x 9 ¾H x 9 ½D 30 lbs.

FRONT PANEL

	Ű,	STANDBY	ŦĦĔŖ₳₽¥	MASTER	BASS		TREBLE	VOLUME	INPUT	Z
1	2	3		4	5	6	7	8	9	

- **1. Power Indicator:** Lights up when power is switched on. If bulb fails replace with type T47.
- 2. Power: Switch up to turn on amplifier. Switch down to turn off amplifier.

3. Stand-By: Leave in off position for 1 minute when powering up the amp. Turn on for play. Place in off position for extended break periods.

- **4. Master:** Controls overall amp volume.
- **5. Bass:** Controls overall low frequency response.
- 6. Mid: Controls overall mid frequency response.
- 7. Treble: Controls overall high frequency response.
- 8. Volume: Controls loudness of amp.
- **9. Input:** Input jack for your guitar.

	CE		SPEAKER OUTPUT CLASS 2 WIRING		A CAUTION AVIS RISK OF ELECTRICAL SHOCK DO NOT OPEN RISQUE DE CHOCE LECTRIQUE	FUSE	
SERIAL NO.		0	0	0	NE PAS OUVRIR	T 2 Amp 250V	• ' , ' • 🛣
MODEL # ZA-37		4 OHM	8 OHM USE ONLY 1 OUTPUT AT A TIME	16 OHM	DATE OF MFG:	1 2 Amp 250V	INPUT POWER 120V
		10	11	12		13	14

REAR PANEL

10. 4 OHM Speaker Jack: Plug in 4 ohm speaker here. Always have a speaker plugged into the amp when it is powered on. Always match the speaker impedance to the proper speaker out jack. This will allow the amp to sound its best and avoid damage.

11.8 OHM Speaker Jack: Plug in 8 ohm speaker here. Always have a speaker plugged into the amp when it is powered on. Always match the speaker impedance to the proper speaker out jack. This will allow the amp to sound its best and avoid damage.

12. 16 OHM Speaker Jack: Plug in 16 ohm speaker here. Always have a speaker plugged into the amp when it is powered on. Always match the speaker impedance to the proper speaker out jack. This will allow the amp to sound its best and avoid damage.

13. Fuse: The fuse protects the amp from electrical faults. Replace only with the same rating and type stated below fuse holder. If the amp repeatedly blows the fuse contact your dealer or Dr Z Amps.

14. AC Inlet: (Class I Wiring). This device is used for disconnection from power mains and must remain readily opearable. The power indicator light does not indicate connection to power mains. The power cord must be disconnected to disconnect amplifier from power mains.

MODEL: _

SERIAL NUMBER: _

INPUT VOLTAGE: _



MADE IN USA



Dr Z Amps 17011 Broadway Ave. Maple Heights, OH 44137 USA

CE

DECLARATION OF CONFORMITY

We, Dr Z Amps, declare, taking this declaration under our total responsibility, that guitar amplifier model Therapy (ZA-37) is in conformity with EN 55013, EN 61000-3-2, EN 61000-3-3, and EN 55020 in accordance with the Directive 2006/95/EC of 12 December 2006, and in conformity with the 2011/65/ECC Rohs Directive.

11-19-2014

Michael Zaite, General Manager Dr Z Amps